

CHEMISTRY BETWEEN US

PL 44-190 Knurów, ul. Przemysłowa 22, phone: +48 32 335 79 00, e-mail: firma@aibsc.com.pl

Seals for wooden windows and doors

Seals for wooden windows and doors are designed for installation in new single frame windows or insulating glass units. They are made of TPS or TPA plastic. These plastics are weldable, which permits for making very tight corners. Seals can also be cut at the corners using special shears offered by our company.

Seals for wooden windows - TPA									
Cross-section	Index	Rabbet height (mm)	Groove height	Groove depth (mm)	Clearance after closing (mm)	Packaging Box (m) Pallet (m)			
			[mm]	(mm) acpenting closing (mm)		Box (mj	T diloc (Trij		
Ð	KDA-7T	12	4-5	8	5	400	2 400		
Ţ	KDA-50	10	3	5	6	100	3 200		
F	KDA-12T	2,5	3	5	6	200	6 400		
	KDA-16	12-19	5	8	-	150	4 800		
Γ	KDA-19	-	5	8	-	200	6 400		
E	KDA-5	12	5	8	5	100	3 200		
P	KDA-9	12	5	8	5	100	3 200		
Ĩ.	KDA-10	12	4	8	4	100	3 200		

Seals for dry glazing of wooden windows TPA							
Cross-section	Index	Cross-section	Ozna Index czenie				
Ł	KDA-34	7	KDA-35				

